

Features

- ◆ Semi-regulated output (load)
- ◆ Industry standard pinout
- ◆ High efficiency up to 88%
- ◆ Single and dual output models
- ◆ I/O isolation voltage 1000 VDC
- ◆ Operationally reliable up to 5'000m altitude
- ◆ Operating temperature range
-40°C to +85°C
- ◆ 3-year product warranty



The TRA 1 series are miniature, I/O-isolated 1W DC/DC-converters with a semi load regulation. They are the ideal solution to power drivers and circuits where unregulated DC/DC converters do not meet the input voltage range at load change.

Models

Order code	Input voltage	Output voltage	Output current max.	Load regulation max.	Efficiency typ.
TRA 1- 0511	5 VDC ±10%	5 VDC	200 mA	6.5 %	84 %
TRA 1- 0519		9 VDC	110 mA	5 %	87 %
TRA 1- 0512		12 VDC	84 mA	5.2 %	87 %
TRA 1- 0513		15 VDC	67 mA	5 %	87 %
TRA 1- 0521		±5 VDC	±100 mA	5.2 %	84 %
TRA 1- 0522		±12 VDC	±42 mA	4.6 %	86 %
TRA 1- 0523		±15 VDC	±34 mA	4.5 %	86 %
TRA 1- 1211	12 VDC ±10%	5 VDC	200 mA	5 %	84 %
TRA 1- 1219		9 VDC	110 mA	3.4 %	86 %
TRA 1- 1212		12 VDC	84 mA	3.4 %	88 %
TRA 1- 1213		15 VDC	67 mA	2.7 %	88 %
TRA 1- 1221		±5 VDC	±100 mA	3.9 %	84 %
TRA 1- 1222		±12 VDC	±42 mA	2.9 %	88 %
TRA 1- 1223		±15 VDC	±34 mA	2.6 %	87 %
TRA 1- 2411	24 VDC ±10%	5 VDC	200 mA	3.7 %	84 %
TRA 1- 2419		9 VDC	110 mA	2.5 %	86 %
TRA 1- 2412		12 VDC	84 mA	2.4 %	87 %
TRA 1- 2413		15 VDC	67 mA	2.3 %	87 %
TRA 1- 2421		±5 VDC	±100 mA	3.7 %	83 %
TRA 1- 2422		±12 VDC	±42 mA	2.4 %	87 %
TRA 1- 2423		±15 VDC	±34 mA	2.3 %	87 %

Input Specifications

Input current no load / full load	5 Vin models	30 mA / 240 mA typ.
	12 Vin models	12 mA / 100 mA typ.
	24 Vin models	11 mA / 50 mA typ.
Surge voltage (1 sec. max.)	5 Vin models	9 V max.
	12 Vin models	18 V max.
	24 Vin models	30 V max.
Reflected input ripple current	12 Vin models	4 mA typ.
	other models	8 mA typ.
Input filter	internal capacitor	
Reverse voltage protection	0.3 A max.	
Recommended input fuse (slow blow type)	5 Vin models:	500 mA
	12 Vin models:	200 mA
	24 Vin models:	100 mA

Output Specifications

Voltage balance (dual output models)	1 % max.	
Regulation	– Input variation	1.05 % / 1 % change of Vin see graph 1 on page 3
	– Load variation	
Ripple and noise (20 MHz Bandwidth)	60 mV pk-pk max.	
Temperature coefficient	± 0.02 %/K	
Short circuit	limited 0.5 sec. max.	
Capacitive load	single output models:	220 µF max.
	dual output models:	100 µF max. (each output)

General Specifications

Temperature ranges	– Operating	–40°C to +85°C (without derating) +105°C max. –50°C to +125°C
	– Case temperature	
	– Storage	
Humidity (non condensing)	95 % rel H max.	
Reliability, calculated MTTF (MIL-HDBK-217F, at +25°C, ground benign)	>2'000'000 h	
Isolation voltage (60 sec.)	Input/Output	1'000 VDC
Isolation capacitance	Input/Output	60 pF typ.
Isolation resistance	Input/Output	>1'000 Mohm
Switching frequency	100 kHz typ. (frequency modulation)	
Frequency change over line and load	–50 / +20 kHz max.	
Altitude during operation	up to 5'000 m (16'400 ft) approved	
Safety standards	IEC 60950-1:2005 (2nd edition) + Am 1:2009 EN 60950-1:2006 + Am 1:2010 + Am 11:2009	
Safety approvals	– CB test report	www.tracopower.com/products/tra-cb.pdf
	– CSA certificate for information technology equipment	

